


# Oil Free Scroll Air Compressors


ANEST IWATA Corporation is the first in the world to develop Air-Cooled, Oil-Free Scroll Compressors, since 1991.



QUALITY PRODUCTS

The ANEST IWATA scroll compressor is extremely quiet (53-60 dB) and safe. The SL Compressors operate according to air consumption and also selects the optimum number of scroll style air-ends to run.

- Quiet (53-60dB)
- Clean-100% Oil-Free air
- Energy Savings
- Multi-stage control system
- Safe
- Smart, compact design



As the orbiting scroll rotates from No.1 position to the No. 4 position the crescent shaped compression room at a semetrical point is gradually reduced, compressed and exhausted through the outlet at the center of the air end.

# Oil Free Scroll Air Compressors

## TECHNICAL SPECIFICATIONS AND DESCRIPTIONS

### SPECIFICATIONS

Model	Motor Rating (HP)	Control System	Control Pressure(PSI)	Free Air Delivery (CFM)	Air Outlet (BSPT)	Outer Dims (Inches)	Weight (lbs)	Noise (dB)
SLP75BS4-236	10	auto start / stop	94-116	30	1/4	26 X 38 X 47	617	53
SLP110ES4-236	15	auto start / stop	94-116	44	3/8	26 X 38 X 47	794	56
SLP150BS4-236	20	auto start / stop	94-116	59	3/4	26 X 38 X 62	1025	58
SLP220BS4-236	30	auto start / stop	87-101	95	1	55 X 45 X 65	1940	59
SLP300BS4-236	40	auto start / stop	87-101	127	1 1/2	55 X 45 X 65	2315	60

### SCROLL BASE MOUNT AIR COMPRESSORS

#### Model SLB

Model	Horse Power (HP)	Phase	Voltage (V)	PRESURE ON-OFF (PSI)	SCFM at 115 PSI (CFM)	Noise (dB)	TANK (GAL)
SLB-2	2	3	208/230/460	85-115	5.3	-	-
SLB-3	3	3	208/230/460	85-115	8.3	-	-
SLB-5	5	3	208/230/460	85-115	14.5	-	-

\* 2HP 1PH 115/208-230V model is available as an optional model.

### SCROLL TANK MOUNT AIR COMPRESSORS




#### Model SLT

Model	Horse Power (HP)	Phase	Voltage (V)	PRESURE ON-OFF (PSI)	SCFM at 115 PSI (CFM)	Noise (dB)	TANK (GAL)
SLT-2	2	3	208/230/460	85-115	5.3	54	60/80
SLT-3	3	3	208/230/460	85-115	8.3	61	60/80
SLT-5	5	3	208/230/460	85-115	14.5	67	60/80

### SCROLL TANK MOUNT ENCLOSURE AIR COMPRESSORS

#### Model SLTE

Model	Horse Power (HP)	Phase	Voltage (V)	PRESURE ON-OFF (PSI)	SCFM at 115 PSI (CFM)	Noise (dB)	TANK (GAL)
SLTE-2	2	3	208/230/460	85-115	5.3	51	60/80
SLTE-3	3	3	208/230/460	85-115	8.3	57	60/80



### ANEST IWATA Air Engineering, Inc.

5325 Muhlhauser Rd  
 West Chester, OH 45011  
 Tel: 513-755-3100 Fax: 513-755-0888  
 Toll Free: 800-440-0282  
 www.anestiwata.com

### DISTRIBUTED BY: